

Robot ABB modello IRB 2600ID-8/2.00 completo di controllo IRC5 SINGLE

CONFIGURAZIONE:

Manipulator protection standard IP67
Manipulator mounting Floor, inverted, wall
Manipulator colour standard Graphite White (RAL7035)
Media outlet at upper arm housing
Connector kit upper arm
Cabinet dimensions 725x710xh970mm
Single cabinet
Cabinet colour RAL 7032
EU Electromagnetic Compatibility
Mains voltage 400V-50Hz
Mains connection type Cable gland
Mains switch Rotary switch
Room temperature Max 45°C
Connectors cover
Manipulator cables lenght 7 m
FlexPendant with 10m cable Basic language English
FlexPendant second language Italian
FlexPendant third language To be defined
Device Net
Auxiliary power supply 24Vdc – 4Amps
Safety signals Internal connection
Operator's panel on cabinet
Operating mode selector Key switch 3 modes
RobotWare5 boot package
Documentation on DVD multilanguage

Kit Motori Mu300 per Track:

N° 1 Motore Mu300 (35 Nm a 4500 rms) + n° 1 Cavo di collegamento tra Armadio IRC5 e Motore di 7 m, n° 1 cavi di 3m tra SMB e base robot, azionamenti tipo W nel quadro robot.
N° 1 Set di cavi a posa mobile per robot (Lunghezza Track 7m).

Opzioni e accessori:

822-2 PROFINET IO M/S SW

SCHEMA I/O (16 ING/16OUT) 716-1 DIGITAL I/O

MONTATO SU SLITTA LUNGHEZZA 7 MT.

